AERONAUTICAL INFORMATION CIRCULAR - MOÇAMBIQUE INSTITUTO DE AVIAÇÃO CIVIL DE MOÇAMBIQUE

DIRECÇÃO DOS SERVIÇOS DE NAVEGAÇÃO AÉREA

AERONAUTICAL INFORMATION SERVICE

Tel: (258) 21-465416 Fax: (258) 21-465415 AFTN: FQHQYSYX iacm@tvcabo.co.mz ais@iacm.gov.mz www.iacm.gov.mz

ALAMEDA DO AEROPORTO Caixa Postal, 227 - Maputo

AIC - International
12/13
27 August

ADVISORY

PROCEDURES FOR APRON MANAGEMENT

1. Authority

This advisory circular is issued by the Executive Chairman of the Institute of Civil Aviation of Mozambique (IACM) in pursuance of powers vested in him under Article 31 of Law 21/2009 of 21 September and Article 12 of Resolution 19/2011 of 30 November.

2. Purpose

This Circular is meant to provide guidelines to the Aerodrome Operator in adopting operation procedures and principles for apron management. The aerodrome operator shall use the combination of these procedures, in order to:

- a) Ensure safe movement with the objective of preventing collisions between aircraft, and between aircraft and obstacles;
- b) Ensure safe entry of aircraft into, and coordinate exit of aircraft from, the apron with the aerodrome control tower; and
- c) Ensure safe and expeditious movement of vehicles and appropriate regulation of other activities.

3. References

ICAO Annex 14 Vol 1 Aerodrome MOZ-CAR Part 139 MOZ-CATS Part 139

4. General

The apron is the area of highest intensity and variety of movements. It is the one place where aircraft, vehicles, passengers, airport employees and sometimes, casual visitors cross and intercross. To ensure that highest level of safety management is maintained and that actual incidences or accident are minimized, the aerodrome operator shall have measures which:

- i. Ensure each service provider on the apron have the safety procedures for the operation service rendered on the apron.
- ii. Ensure that all employees working on the apron are indoctrinated in the principles and practices of safety and tested on that knowledge before working on the apron.
- iii. Have in place a programme of periodically reviewing and checking:
- iv. Accuracy of safety record and data on the apron.
- v. The validity of the safety procedures.
- vi. Safety awareness and practices of each employee working on the apron.
- vii. For safety management purpose operator of aerodrome shall make available the surface marking and signage to communicate safety information that abide passengers, drivers of vehicles and equipments and airport staff on the apron.
- viii. Ensure that access to the aprons by personnel and vehicles are limited to only those that have been specifically and individually cleared to work on the apron.
- viiii. Ensure that each person working on the apron reports incidence or accidents of unsafe practice that has been observed.
- x. Ensures any personnel, who had been approved to work at certain portions of the manoeuvring area, do not stray outside the demarcated approved area of works and that Permission are obtained from Air Traffic Controller if personnel are required to go beyond the approved boundaries;
- xi Ensures any airside organization which requires outside personnel or contractors to their premises abides to the terms and conditions associated with the issue of airport pass and the general rules applicable to pedestrians and workers in the airside and that they adhere strictly to the rules and procedures governing the airside;

AIC 12/13 Page 2 of 5

- xii. Ensure any organization contracted to work on the airside area submit Safety Management Plan that shall be in force for the whole period of contract. As a minimum the safety plan shall include the following:
- 1. Training on safety in relation to:
 - a) Hazards to himself/herself and others emanating from his/her occupation.
 - b) Hazards to equipments, other employees and third parties, structures and installations.
- 2. Issue and enforce the wearing of approved safety protective equipment.
- 3. Make provision or procedures for handling of accidents and injury to its personnel.
- 4. Provide the name and other details of the person designated as the Safety Officer for the firm.
- 5. Plan for giving its staff refresher course on safety at least once every 6 months.

Co-ordination with Air Traffic Services

- a) The transfer points of responsibility between TWR and Apron Management are at the holding points of the taxiways.
- b) For arriving aircraft the TWR controller shall release the aircraft to apron control after it crosses the points indicated in (a) above. However he may release the aircraft earlier once the pilot reports that he has the marshalled in sight.
- c) For departing aircraft the marshalled shall release the aircraft to TWR before it crosses the transfer points in (a) above. However he may release the aircraft earlier once it is definitely heading to the taxiway and is clear of all obstacles.
- d) TWR or the Briefing Unit shall inform Apron Management the ETA of each arriving aircraft and, if not otherwise indicated, the apron of its destination. TWR shall advise the Apron Control the landing of each aircraft as soon as it touches down.

AIC 12/13 Page 3 of 5

e) Apron Management shall advise the TWR of the aircraft stand or place that it has allocated to an arriving aircraft as early as possible and before it reaches the point of transfer of control.

5. Allocation of Aircraft stands

- a) Allocation of Aircraft Stands or parking bays is the responsibility of the aerodrome operator.
- b) In assessing the demand for aircraft stands on particular day or for a particular period of that day, the aerodrome operator shall consider:
 - i) The scheduled aircraft movement.
 - ii) The number of stands already occupied by aircraft especially those whose departure have been delayed, and.
- c) In allocating stands or bays, the aerodrome operator shall consider the following:
 - i) The type of aircraft i.e. weight, wingspan, fuselage length, fueling requirements etc.
 - ii) The airports movement schedule for the day.
 - iii) The principle of first come first served.
 - iv) Duration of the intended parking.

Rules and Procedures for Aircraft marshalling.

Marshalling is a service provided to an arriving aircraft so that it can move safely from the edge of the apron to its allocated parking stand/bay and from that position to the edge of the apron when it departs.

The marshalling of aircraft shall be carried out in accordance to the provisions adopted from ICAO Annex 2 Chapter 3. The marshalling and parking of aircraft shall ensure that aircraft are guided and parked clear of other aircraft, vehicles, and fixed or stationery objects by at least the following margins:

AIC 12/13 Page 4 of 5

1) Light aircraft - 3 meters

2) Mid size aircraft - 4.5 meters

3) Large aircraft - 7.5 meters

6. Procedures for Engine Start – up

Pilot normally seeks from the control tower a clearance to start up engines. Before allowing an aircraft to start engines, the aerodrome operator through the designated officer or an aircraft operator's engineer shall ensure that the aircraft is in a state in which it can safely do so in relation to people and equipment around and behind the aircraft.

7. Leader Van Service (Follow-Me)

Aerodrome operator shall develop procedures for leader van (Follow-Me) Service to provide guidance on movement areas of aerodrome for:

- a) Vehicles operation not familiar with apron layout;
- b) An experienced pilot when taxing in imperfect visibility condition; and
- c) Any other situations deemed leader van services necessary.

INSTITUTE OF CIVIL AVIATION OF MOZAMBIQUE

THE CHAIRMAN OF THE BOARD AND CEO

Capt João Martins de Abreu